

ConTEXt

title : ConTEXt User Module
subtitle : Something like KOMA-TypeArea
author : Peter Münster
date : April 5, 2008


```

1 \writestatus{loading}{Something like KOMA-TypeArea}
2 \unprotect

```

\setupType... Setting up some values.

Default setup:

```
\setupTypeArea[bcor=0pt,oneside=no,alphabets=2.6]
```

Example:

```
\setupTypeArea[bcor=3mm,oneside=yes,alphabets=3.1]
```

```
3 \def\setupTypeArea[#1]{\getparameters[T@]{#1}\doTypeArea}
```

Some internal dimensions:

```
4 \newdimen\PageWidth \newdimen\Back
\doifundefined{Width}{\newdimen\Width}
\doifundefined{Height}{\newdimen\Height}
```

This internal macro does the whole work:

```
5 \def\doTypeArea{
```

Set visible page width:

```
6 \PageWidth=\dimexpr\paperwidth-\TA@bcor\relax
```

Determine the paper aspect ratio:

```
7 \edef\Ratio{\withoutpt{\the\dimexpr2\paperheight/(\PageWidth/32768)\relax}}
```

Set the textarea width to X alphabets:

```
8 \setbox\scratchbox\hbox{\dorecuse{26}{\character\recurselevel}}
\Width=\dimexpr\TA@alphabets\wd\scratchbox\relax
\ifdim\Width<\PageWidth\else
\writestatus{error}{line wider than page}\end\fi
```

Set the textarea height proportional to the width:

```
9 \Height=\dimexpr(\Ratio\Width)
```

Set the margin/gutter widths to be equal on a full spread:

```
10 \doifelse{\TA@oneside}{yes}
{\Back=\dimexpr(\PageWidth - \Width) / 2 + \TA@bcor\relax}
{\Back=\dimexpr(\PageWidth - \Width) / 3 + \TA@bcor\relax}
```

Set the top and bottom margins in a 1:2 ratio, ignoring headers:

```
11 \edef\Top{\the\dimexpr(\paperheight - \Height) / 3 - 3\lineheight\relax}
```

Redefine \Height to include header and footer space:

Something like KOMA-TypeArea

```
12 \Height=\dimexpr(\Height + 8\lineheight)

Set up the page layout using the calculated parameters:

13 \setuplayout[
    backspace=\the\Back,
    height=\the\Height,
    width=\the\Width,
    header=2\lineheight,
    headerdistance=\lineheight,
    footer=2\lineheight,
    footerdistance=3\lineheight,
    topspace=\Top]
}

\protect

14 \setupTypeArea[bcor=0pt,oneside=no,alphabets=2.6]

15 \doifnotmode{demo}{\endinput}
```

Usage example:

```
16 \usemodule[typearea]
\setupTypeArea[bcor=0mm,alphabets=3.1]
\setuppagenumbers[alternative=doublesided]
\starttext
\dorecurse4{\framed[width=\textwidth,height=\textheight]{test}\page}
\stoptext
```

Something like KOMA-TypeArea

```
\setupTypeArea 1
```

