

# L<sup>A</sup>T<sub>E</sub>X News, Issues 1–17

## Contents

<b>Issue 1, June 1994</b>	<b>3</b>	<b>Issue 6, December 1996</b>	<b>8</b>
Welcome to L <sup>A</sup> T <sub>E</sub> X News . . . . .	3	Welcome to L <sup>A</sup> T <sub>E</sub> X News 6 . . . . .	8
L <sup>A</sup> T <sub>E</sub> X 2 <sub>ε</sub> —the new L <sup>A</sup> T <sub>E</sub> X release . . . . .	3	Mono-case file names . . . . .	8
Why a new L <sup>A</sup> T <sub>E</sub> X? . . . . .	3	Another input encoding . . . . .	8
Processing documents with L <sup>A</sup> T <sub>E</sub> X 2 <sub>ε</sub> . . . . .	3	Better user-defined math display environments . . . . .	8
New packages . . . . .	3	Docstrip improvements . . . . .	8
Further information . . . . .	3	AMS L <sup>A</sup> T <sub>E</sub> X update . . . . .	8
		Graphics package update . . . . .	8
		EC Fonts released . . . . .	8
<b>Issue 2, December 1994</b>	<b>4</b>	<b>Issue 7, June 1997</b>	<b>9</b>
Welcome to L <sup>A</sup> T <sub>E</sub> X News 2 . . . . .	4	T1 encoded Computer Modern fonts . . . . .	9
December 1994 release of L <sup>A</sup> T <sub>E</sub> X . . . . .	4	T1 encoded Concrete fonts . . . . .	9
Accented input . . . . .	4	Further input encodings . . . . .	9
AMS-L <sup>A</sup> T <sub>E</sub> X . . . . .	4	Normalising spacing after punctuation . . . . .	9
L <sup>A</sup> T <sub>E</sub> X on the internet . . . . .	4	Accessing Bold Math Symbols . . . . .	9
Further information . . . . .	4	Policy on standard classes . . . . .	9
		New addresses for TUG . . . . .	9
<b>Issue 3, June 1995</b>	<b>5</b>	<b>Issue 8, December 1997</b>	<b>10</b>
Welcome to L <sup>A</sup> T <sub>E</sub> X News 3 . . . . .	5	New supported font encodings . . . . .	10
June 1995 release of L <sup>A</sup> T <sub>E</sub> X . . . . .	5	New input encodings . . . . .	10
Additional input encodings . . . . .	5	Tools . . . . .	10
L <sup>A</sup> T <sub>E</sub> X getting smaller . . . . .	5	Graphics . . . . .	10
Distribution and modification . . . . .	5	L <sup>A</sup> T <sub>E</sub> X3 experimental programming conventions . . . . .	10
AMS-L <sup>A</sup> T <sub>E</sub> X full release . . . . .	5	<b>Issue 9, June 1998</b>	<b>11</b>
PostScript fonts . . . . .	5	New math font encodings . . . . .	11
Further information . . . . .	5	A new math accent . . . . .	11
		Extended <code>\DeclareMathDelimiter</code> . . . . .	11
<b>Issue 4, December 1995</b>	<b>6</b>	Tools distribution . . . . .	11
Welcome to L <sup>A</sup> T <sub>E</sub> X News 4 . . . . .	6	Support for Cyrillic encodings . . . . .	11
L <sup>A</sup> T <sub>E</sub> X getting smaller . . . . .	6	Default docstrip header . . . . .	11
New ‘concurrent’ docstrip . . . . .	6	<b>Issue 10, December 1998</b>	<b>12</b>
New T1 encoded fonts . . . . .	6	Five years of L <sup>A</sup> T <sub>E</sub> X 2 <sub>ε</sub> . . . . .	12
More robust commands . . . . .	6	Restructuring the L <sup>A</sup> T <sub>E</sub> X distribution . . . . .	12
New Interface to building ‘extension’ classes . . . . .	6	L <sup>A</sup> T <sub>E</sub> X Project on the Internet . . . . .	12
More Input Encodings . . . . .	6	Restructuring the L <sup>A</sup> T <sub>E</sub> X package licenses . . . . .	12
Further information . . . . .	6	Support for Cyrillic encodings . . . . .	12
		Tools distribution . . . . .	12
<b>Issue 5, June 1996</b>	<b>7</b>	<b>Issue 11, June 1999</b>	<b>13</b>
Welcome to L <sup>A</sup> T <sub>E</sub> X News 5 . . . . .	7	Back in sync . . . . .	13
Extra possibilities for section headings . . . . .	7	Yearly release cycles . . . . .	13
The ‘openany’ option in the ‘book’ class . . . . .	7	LPPL update . . . . .	13
More font (output) encodings . . . . .	7	The future of SliT <sub>E</sub> X . . . . .	13
More input encodings supported . . . . .	7	Fontenc package peculiarities . . . . .	13
Fixes and improvements . . . . .	7	New math font encodings . . . . .	13
Changes to the ‘tools’ packages . . . . .	7	Tools distribution . . . . .	13
New copy of the L <sup>A</sup> T <sub>E</sub> X bug database . . . . .	7	Coming soon . . . . .	13

<b>Issue 12, December 1999</b>	<b>14</b>
LPPL update . . . . .	14
fixltx2e package . . . . .	14
Outcome of TUG '99 (Vancouver) . . . . .	14
<b>Issue 13, June 2000</b>	<b>15</b>
Yearly release cycle . . . . .	15
PSNFSS: Quote of the Month . . . . .	15
New AMS- $\text{\LaTeX}$ . . . . .	15
New input encoding <code>latin4</code> . . . . .	15
New experimental code . . . . .	15
<b>Issue 14, June 2001</b>	<b>16</b>
Future releases . . . . .	16
New release of <code>Babel</code> (required) . . . . .	16
New input encoding <code>latin9</code> . . . . .	16
New tools . . . . .	16
New experimental code . . . . .	16
<b>Issue 15, December 2003</b>	<b>17</b>
Anniversary release . . . . .	17
LPPL – new version . . . . .	17
Small updates to <code>varioref</code> . . . . .	17
New and more robust commands . . . . .	17
Fixing font sizes . . . . .	17
Font encodings . . . . .	17
Displaying font tables . . . . .	17
New input encodings . . . . .	17
Unicode input . . . . .	17
And finally ... <code>pict2e</code> . . . . .	17
<b>Issue 16, December 2003</b>	<b>18</b>
Anniversary news . . . . .	18
TLC2: The $\text{\LaTeX}$ Companion – 2nd edition! . . . . .	18
Future maintenance . . . . .	18
LPPL certification . . . . .	18
Use of $\epsilon\text{-TeX}$ / <code>pdfTeX</code> . . . . .	18
End of ‘autoload’ support . . . . .	18
New models, new code . . . . .	18
<b>Issue 17, December 2005</b>	<b>19</b>
Project licence news . . . . .	19
New guide on font encodings . . . . .	19
Robust commands in <code>math</code> . . . . .	19
Updates of required packages . . . . .	19
Work on $\text{\LaTeX}$ fixes . . . . .	19
The graphics bundle . . . . .	20
Future development . . . . .	20

# L<sup>A</sup>T<sub>E</sub>X News

Issue 1, June 1994

## Welcome to L<sup>A</sup>T<sub>E</sub>X News

An issue of *L<sup>A</sup>T<sub>E</sub>X News* will accompany every future release of L<sup>A</sup>T<sub>E</sub>X. It will tell you about important events, such as major bug fixes, newly available packages, or any other L<sup>A</sup>T<sub>E</sub>X news.

## L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>—the new L<sup>A</sup>T<sub>E</sub>X release

The most important news is the release of L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>, the new version of the L<sup>A</sup>T<sub>E</sub>X software. This version has better support for fonts, graphics and colour, and will be actively maintained by the L<sup>A</sup>T<sub>E</sub>X3 project team. Upgrades will be issued every six months, in June and December.

## Why a new L<sup>A</sup>T<sub>E</sub>X?

Over the years many extensions have been developed for L<sup>A</sup>T<sub>E</sub>X. This is, of course, a sure sign of its continuing popularity but it has had one unfortunate result: incompatible L<sup>A</sup>T<sub>E</sub>X formats came into use at different sites. Thus, to process documents from various places, a site maintainer was forced to keep L<sup>A</sup>T<sub>E</sub>X (with and without NFSS), S<sup>L</sup>I<sup>T</sup>E<sup>X</sup>,  $\mathcal{A}\mathcal{M}\mathcal{S}$ -L<sup>A</sup>T<sub>E</sub>X, and so on. In addition, when looking at a source file it was not always clear for which format the document was written.

To put an end to this unsatisfactory situation a new release of L<sup>A</sup>T<sub>E</sub>X was produced. It brings all such extensions back under a single format and thus prevents the proliferation of mutually incompatible dialects of L<sup>A</sup>T<sub>E</sub>X 2.09. The new release was available for several months as a test version, and the final release of 1 June officially replaces the old version.

## Processing documents with L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>

Documents written for L<sup>A</sup>T<sub>E</sub>X 2.09 will still be read by L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>. Any such document is run in *L<sup>A</sup>T<sub>E</sub>X 2.09 compatibility mode*.

Unfortunately, compatibility mode comes with a price: it can run up to 50% slower than L<sup>A</sup>T<sub>E</sub>X 2.09 did. If you want to run your document in the faster *native mode*, you should try replacing the line:

```
\documentstyle[options,packages]{class}
```

with:

```
\documentclass[options]{class}  
\usepackage{latexsym,packages}
```

Unfortunately, this will not always work, because some L<sup>A</sup>T<sub>E</sub>X 2.09 packages will only work in L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> compatibility mode. You should find out if there is a L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> version of the package available.

L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> native mode also gives access to the new features of L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>, described in *L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> for authors*.

## New packages

L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> has much better support for graphics, colour, fonts, and multi-lingual typesetting. The following software should be available from the distributor who brought you L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>:

*babel*, for typesetting in many languages.

*color*, for colour support.

*graphics*, for including images.

*mfnfss*, for using bitmap fonts.

*psnfss*, for using Type 1 fonts.

*tools*, other packages by the L<sup>A</sup>T<sub>E</sub>X3 team.

The packages come with full documentation, and are also described in *L<sup>A</sup>T<sub>E</sub>X: A Document Processing System* or *The L<sup>A</sup>T<sub>E</sub>X Companion*.

## Further information

More information about L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> is to be found in:

*L<sup>A</sup>T<sub>E</sub>X: A Document Preparation System*, Leslie Lamport, Addison Wesley, 2nd ed, 1994.

*The L<sup>A</sup>T<sub>E</sub>X Companion*, Goossens, Mittelbach and Samarin, Addison Wesley, 1994.

The L<sup>A</sup>T<sub>E</sub>X distribution comes with documentation on the new features of L<sup>A</sup>T<sub>E</sub>X:

*L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> for authors*, describes the new features of L<sup>A</sup>T<sub>E</sub>X documents, in the file `usrguide.tex`.

*L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> for class and package writers*, describes the new features of L<sup>A</sup>T<sub>E</sub>X classes and packages, in the file `clsguide.tex`.

*L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> font selection*, describes the new features of L<sup>A</sup>T<sub>E</sub>X fonts for class and package writers, in the file `fntguide.tex`.

For more information on T<sub>E</sub>X and L<sup>A</sup>T<sub>E</sub>X, get in touch with your local T<sub>E</sub>X Users Group, or the international T<sub>E</sub>X Users Group, P. O. Box 869, Santa Barbara, CA 93102-0869, USA, Fax: +1 805 963 8358, EMail: [tug@tug.org](mailto:tug@tug.org).

# L<sup>A</sup>T<sub>E</sub>X News

Issue 2, December 1994

## *Welcome to L<sup>A</sup>T<sub>E</sub>X News 2*

An issue of *L<sup>A</sup>T<sub>E</sub>X News* will accompany every future release of L<sup>A</sup>T<sub>E</sub>X. It will tell you about important events, such as major bug fixes, newly available packages, or any other L<sup>A</sup>T<sub>E</sub>X news.

## *December 1994 release of L<sup>A</sup>T<sub>E</sub>X*

December 1994 sees the second release of L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>. We are on schedule to deliver a release of L<sup>A</sup>T<sub>E</sub>X every six months, in December and June.

This release has seen quite a lot of activity, which is not too surprising as it's only been a year since the first test release of L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>. We don't expect so much activity in the next six months.

Many of the changes are minor improvements and bug-fixes—see *L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> for authors* (`usrguide.tex`), *L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> font selection* (`fntguide.tex`) and our change log (`changes.txt`) for more details.

However, there are two important new packages available for L<sup>A</sup>T<sub>E</sub>X: `inputenc` and AMS-L<sup>A</sup>T<sub>E</sub>X.

## *Accented input*

One of the problems with writing non-English documents in L<sup>A</sup>T<sub>E</sub>X is the accent commands. Reading documents containing text like `na\~i ve` is frustrating, especially if your keyboard allows you to type `naïve`.

In the past, L<sup>A</sup>T<sub>E</sub>X has not supported input containing accented characters such as `ï`, because Windows, Macintosh and Unix all have different ways of dealing with accented input, called *input encodings*.

However, the `inputenc` package allows you to specify which input encoding your document is written with, for example to use the ISO Latin-1 encoding, you type:

```
\usepackage[latin1]{inputenc}
```

At the moment, `inputenc` supports the `ascii` and `latin1` input encodings, but more will be added with future releases.

The `inputenc` package is currently a test release. The user interface for the full release will be upwardly compatible with the test version.

## *AMS-L<sup>A</sup>T<sub>E</sub>X*

AMS-L<sup>A</sup>T<sub>E</sub>X is a set of miscellaneous extensions for L<sup>A</sup>T<sub>E</sub>X distributed by the American Mathematical Society. They provide superior information structure

and superior printed output for mathematical documents.

There are far too many features of AMS-L<sup>A</sup>T<sub>E</sub>X to list here. AMS-L<sup>A</sup>T<sub>E</sub>X is described in the accompanying documentation, and in *The L<sup>A</sup>T<sub>E</sub>X Companion*.

Version 1.2beta of AMS-L<sup>A</sup>T<sub>E</sub>X was released for testing by intrepid users in October 1994. The full release of AMS-L<sup>A</sup>T<sub>E</sub>X 1.2 is expected in early January 1995.

It will be divided into two bundles:

- the `amsfonts` packages, which give access to hundreds of new mathematical symbols, and new math fonts such as blackboard bold and fraktur.
- the `amsmath` packages, which provide finer control over mathematical typesetting, such as multi-line subscripts, enhanced theorem and proof environments, and improved displayed equations,

For compatibility with older documents, an `amstex` package will be provided.

## *L<sup>A</sup>T<sub>E</sub>X on the internet*

L<sup>A</sup>T<sub>E</sub>X has its own home page on the World Wide Web, with the URL:

<http://www.tex.ac.uk/CTAN/latex/>

This page describes L<sup>A</sup>T<sub>E</sub>X and the L<sup>A</sup>T<sub>E</sub>X3 project, and contains pointers to other L<sup>A</sup>T<sub>E</sub>X resources, such as the user guides, the T<sub>E</sub>X Frequently Asked Questions, and the L<sup>A</sup>T<sub>E</sub>X bugs database.

The electronic home of anything T<sub>E</sub>X-related is the Comprehensive T<sub>E</sub>X Archive Network (CTAN). This is a network of cooperating ftp sites, with over a gigabyte of T<sub>E</sub>X material:

```
ftp://ftp.tex.ac.uk/tex-archive/  
ftp://ftp.shsu.edu/tex-archive/  
ftp://ftp.dante.de/tex-archive/
```

For more information, see the L<sup>A</sup>T<sub>E</sub>X home page.

## *Further information*

For more information on T<sub>E</sub>X and L<sup>A</sup>T<sub>E</sub>X, get in touch with your local T<sub>E</sub>X Users Group, or the international T<sub>E</sub>X Users Group, P. O. Box 869, Santa Barbara, CA 93102-0869, USA, Fax: +1 805 963 8358, EMail: [tug@tug.org](mailto:tug@tug.org).

# L<sup>A</sup>T<sub>E</sub>X News

Issue 3, June 1995

## *Welcome to L<sup>A</sup>T<sub>E</sub>X News 3*

An issue of *L<sup>A</sup>T<sub>E</sub>X News* will accompany every future release of L<sup>A</sup>T<sub>E</sub>X. It will tell you about important events, such as major bug fixes, newly available packages, or any other L<sup>A</sup>T<sub>E</sub>X news.

## *June 1995 release of L<sup>A</sup>T<sub>E</sub>X*

June 1995 sees the third release of L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>. We are on schedule to deliver a release of L<sup>A</sup>T<sub>E</sub>X every six months, in December and June.

In the last *L<sup>A</sup>T<sub>E</sub>X News*, we said “we don’t expect so much activity in the next six months,” which has turned out not to be true!

## *Additional input encodings*

In the last release of L<sup>A</sup>T<sub>E</sub>X we distributed a test version of the `inputenc` package which allows the use of input characters other than just a–z and A–Z. The package has proved to be robust, so we are now distributing an expanded version. The new release comes with a number of input encodings:

- `ascii` the standard encoding,
- `latin1` the ISO Western European alphabet,
- `latin2` the ISO Eastern European alphabet,
- `cp437` the IBM codepage 437,
- `cp850` the IBM codepage 850, and
- `applemac` the Apple Macintosh encoding.

These can be used by specifying an option to the `inputenc` package, for example:

```
\usepackage[latin1]{inputenc}
```

The new input encodings are currently being tested, but we don’t expect any major changes.

## *L<sup>A</sup>T<sub>E</sub>X getting smaller*

In the past releases of L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>, the amount of memory L<sup>A</sup>T<sub>E</sub>X requires has increased, but we are pleased to say that this trend has been reversed. We hope that future releases of L<sup>A</sup>T<sub>E</sub>X will continue to get smaller.

For example, on this document, the December 1994 release used 52,622 words of memory, and the June 1995 release uses 51,216 words of memory, which is a 2.7% reduction.

We are currently experimenting with other ways of reducing the size of L<sup>A</sup>T<sub>E</sub>X. For example, we are experimenting with an option to remove the `picture` and `tabbing` environments from the L<sup>A</sup>T<sub>E</sub>X kernel, and to load them from a file the first time they are used. This should help L<sup>A</sup>T<sub>E</sub>X to run on machines with limited memory. See `autoload.txt` for details.

## *Distribution and modification*

One topic of discussion that has kept us busy is the distribution and modification conditions of L<sup>A</sup>T<sub>E</sub>X. We are committed to keeping L<sup>A</sup>T<sub>E</sub>X as free reliable software, and ensuring that (as far as possible) L<sup>A</sup>T<sub>E</sub>X documents will produce the same results on all systems.

The modification conditions are currently under discussion, and we would like to hear from anyone interested. Please read `modguide.tex` for more information.

## *AMS-L<sup>A</sup>T<sub>E</sub>X full release*

The AMS-L<sup>A</sup>T<sub>E</sub>X packages were still in beta test in the December 1994 release of L<sup>A</sup>T<sub>E</sub>X, and the full release came out in January 1995.

AMS-L<sup>A</sup>T<sub>E</sub>X is described in the *User’s Guide* (`amslatex.tex`) and in *The L<sup>A</sup>T<sub>E</sub>X Companion*.

## *PostScript fonts*

There is a new test release of the PSNFSS packages for accessing PostScript fonts in L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>. This includes an update to all of the fonts, to remove many of the underfull and overfull `\hbox` warnings, and improve the setting of non-English languages.

The new release of L<sup>A</sup>T<sub>E</sub>X removes all of the ‘hidden’ uses of Computer Modern mathematics. For example, the footnote markers used to use math mode, so always used Computer Modern digits rather than ones from the current text font. This has now been fixed.

## *Further information*

For more information on T<sub>E</sub>X and L<sup>A</sup>T<sub>E</sub>X, get in touch with your local T<sub>E</sub>X Users Group, or the international T<sub>E</sub>X Users Group, P. O. Box 869, Santa Barbara, CA 93102-0869, USA, Fax: +1 805 963 8358, EMail: [tug@tug.org](mailto:tug@tug.org).

The L<sup>A</sup>T<sub>E</sub>X home page is <http://www.tex.ac.uk/ctan/latex/> and contains links to other WWW resources for L<sup>A</sup>T<sub>E</sub>X.

# L<sup>A</sup>T<sub>E</sub>X News

Issue 4, December 1995

## *Welcome to L<sup>A</sup>T<sub>E</sub>X News 4*

An issue of *L<sup>A</sup>T<sub>E</sub>X News* will accompany every future release of L<sup>A</sup>T<sub>E</sub>X. It will tell you about important events, such as major bug fixes, newly available packages, or any other L<sup>A</sup>T<sub>E</sub>X news. This issue accompanies the fourth release of L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>.

## *L<sup>A</sup>T<sub>E</sub>X getting smaller*

The last release in June started a trend of L<sup>A</sup>T<sub>E</sub>X becoming smaller, we are pleased to announce that this has continued with this release. In particular the experimental ‘autoload’ version described in `autoload.txt` is much smaller as more parts of L<sup>A</sup>T<sub>E</sub>X are autoloaded.

## *New ‘concurrent’ docstrip*

The time taken to ‘unpack’ this release from the documented sources should be much reduced (roughly half the time, depending on installation conditions). This is due to an improved version of the docstrip program that has been contributed by Marcin Woliński. This can write up to 16 files at once. The previous version could only write one file at a time which meant that it was very slow when producing many small files from the same source file as the source needed to be re-read for each file written.

## *New T1 encoded fonts*

This year Jörg Knappen has completed a new release of the ‘Cork’ (T1) encoded Computer Modern fonts: the dc fonts release 1.2.

This release of the dc fonts fixes many bugs (including the missing ? ‘(i) and ! ‘(i) ligatures) and improves the fonts in many other ways. It is strongly recommended that you upgrade as soon as possible if currently you are using the old dc fonts, release 1.1 or earlier. The new fonts are available from the CTAN archives, in `tex-archive/fonts/dc`.

The names of the font files are *different*. This does not affect L<sup>A</sup>T<sub>E</sub>X documents but *does* affect the installation procedure as it assumes that you have the *new* fonts, and will write suitable ‘fd’ files for those fonts. If you have not yet upgraded your dc fonts then, after unpacking the distribution, you *must* `latex olddc.ins` to produce ‘fd’ files for the old dc fonts. This must be done *before* the format is made. Running the test document at `ltxcheck.tex` the end of

the installation will inform you if the wrong set of ‘fd’ files has been installed.

Note that this change does not affect the standard ‘OT1’ Computer Modern fonts that L<sup>A</sup>T<sub>E</sub>X uses by default.

## *More robust commands*

The commands `\cite` and `\sqrt` are now robust.

Although most commands with optional arguments are fragile, as documented, such commands defined using the second optional argument of `\newcommand` and its derivatives are now *robust*.

## *New Interface to building ‘extension’ classes*

The mechanism provided by `\DeclareOption`, `\ProcessOptions` and `\LoadClass` has proved to be a powerful and expressive means of defining one class in terms of another ‘base’ class. However there have been some requests to simplify the declaration of the common case where you want the ‘base’ class to be called with *all* the options that were specified to the extension class. This is now provided by the new command `\LoadClassWithOptions`. A similar command `\RequirePackageWithOptions` is provided for package use. More details of this feature are provided in `clsguide.tex` and `ltclass.dtx`.

## *More Input Encodings*

The experimental `inputenc` package allows a more natural style of input of accented and other characters.

Three new input encodings are now supported.

- **ansinew** the Windows ansi encoding, as used in Microsoft Windows 3.x.
- **cp437de** a variant of `cp437`, which uses  $\beta$  rather than  $\beta$  in the appropriate slot.
- **next** the encoding used on Next computers.

## *Further information*

For more information on T<sub>E</sub>X and L<sup>A</sup>T<sub>E</sub>X, get in touch with your local T<sub>E</sub>X Users Group, or the international T<sub>E</sub>X Users Group, 1850 Union Street, #1637, San Francisco, CA 94123, USA, Fax: +1 415 982 8559, Email: [tug@tug.org](mailto:tug@tug.org). The L<sup>A</sup>T<sub>E</sub>X home page is <http://www.tex.ac.uk/ctan/latex/> and contains links to other WWW resources for L<sup>A</sup>T<sub>E</sub>X.

# L<sup>A</sup>T<sub>E</sub>X News

Issue 5, June 1996

## Welcome to L<sup>A</sup>T<sub>E</sub>X News 5

This issue of *L<sup>A</sup>T<sub>E</sub>X News* accompanies the fifth release of the new standard L<sup>A</sup>T<sub>E</sub>X, L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>.

## Extra possibilities for section headings

Most L<sup>A</sup>T<sub>E</sub>X sectioning commands are defined using `\@startsection`. For example, the article class defines:

```
\newcommand\section{\@startsection
{section}{1}{0pt}{-3.5ex plus-1ex minus-.2ex}%
{2.3ex plus.2ex}{\normalfont\Large\bfseries}}
```

The last argument specifies the style in which the section heading is to be typeset.

The new feature added at this release is that at the *end* of this argument you may specify a command that *takes an argument*. This command will be applied to the section number and heading. For example, one could use the `\MakeUppercase` command to produce uppercase headings. A package or class file could contain:

```
\renewcommand\section{\@startsection
{section}{1}{0pt}{-3.5ex plus-1ex minus-.2ex}%
{2.3ex plus.2ex}{\normalfont\Large\MakeUppercase}}
```

to produce section headings using uppercase medium weight text, rather than the bold text used by article. Note that, like the font choice, the uppercasing applies only to the actual heading (including any automatically generated section number), not to the text as it may appear in the running head or table of contents.

## The ‘openany’ option in the ‘book’ class

The `openany` option allows chapter and similar openings to occur on left hand pages. Previously this option only affected `\chapter` and `\backmatter`. It now also affects `\part`, `\frontmatter` and `\mainmatter`.

## More font (output) encodings

The font encoding name T3 has been allocated to the encoding used in the new 256-character IPA fonts (for the phonetic alphabet) produced by Rei Fukui. His package, `tipa`, gives access to these fonts and should soon be available. (The encoding named OT3 is the 128-character encoding used in the IPA fonts produced by Washington State University.)

## More input encodings supported

The `inputenc` package now supports the IBM codepage 852 used in Eastern Europe, with the option `[cp852]` contributed by Petr Sojka.

Also, the `inputenc` package now activates most ‘control codes’ with ASCII values below 32. Currently none of the encodings in the standard distribution makes use of these positions.

## Fixes and improvements

The L<sup>A</sup>T<sub>E</sub>X kernel has only had minor changes, apart from `\@startsection` mentioned above. However, some small fixes have been incorporated removing the following problems:

- In `tabular` and `array`, previous versions of L<sup>A</sup>T<sub>E</sub>X ‘lost’ the inter-column space from an ‘1’-column, when that column was completely empty.
- Previously, the use of the `\nofiles` command could change the *vertical spacing* in a document. A side effect of fixing this is that when `\nofiles` is used, `\label` puts a blank line in the log file.
- L<sup>A</sup>T<sub>E</sub>X often loads fonts ‘on demand’. Previously, this could happen inside the argument of an accent command and this would cause the accent to appear in the wrong place.

## Changes to the ‘tools’ packages

- The `longtable` package now uses a modified algorithm, contributed by David Kastrup, to align the ‘chunks’ of a table. It is now unnecessary to edit the document to add `\setlongtables` before the final run of L<sup>A</sup>T<sub>E</sub>X. In certain cases of overlapping `\multicolumn` entries, the new algorithm will produce better column widths than the old (at the price of extra passes through L<sup>A</sup>T<sub>E</sub>X).
- The `dcolumn` package now has the extra possibility of specifying the number of digits both *before* and *after* the ‘decimal point’. This makes it easy to centre the column of numbers under a wide heading.

## New copy of the L<sup>A</sup>T<sub>E</sub>X bug database

<http://www.tex.ac.uk/ctan/latex/bugs.html> will soon have links to a copy of the searchable L<sup>A</sup>T<sub>E</sub>X bugs database at Mainz (Germany) as well as the original copy at Sussex (England).

# L<sup>A</sup>T<sub>E</sub>X News

Issue 6, December 1996

## Welcome to L<sup>A</sup>T<sub>E</sub>X News 6

This issue of *L<sup>A</sup>T<sub>E</sub>X News* accompanies the sixth release of the new standard L<sup>A</sup>T<sub>E</sub>X, L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>.

### Mono-case file names

Previously L<sup>A</sup>T<sub>E</sub>X has used some files with ‘mixed-case’ file names such as `T1cmr.fd` and `T1enc.def`.

These file names cause problems on some systems (in particular they are illegal on the ISO 9660 CDROM format) and so in this release all file names have been made lowercase (for example `t1cmr.fd` and `t1enc.def`).

This change should *not* affect any document. Within L<sup>A</sup>T<sub>E</sub>X, encodings still have the usual uppercase names in uses such as `\usepackage[T1]{fontenc}` and `\fontencoding{T1}`. L<sup>A</sup>T<sub>E</sub>X will automatically convert to the lowercase form while constructing the file name. L<sup>A</sup>T<sub>E</sub>X will input the ‘fd’ file under the old name if it fails to find the file with the new name, so existing collections of fd files should still work with this new release.

The change *does* affect the configuration files that may be used to make the L<sup>A</sup>T<sub>E</sub>X format with `initex`. For example, the file `fonttext.ltx` previously specified `\input{T1cmr.fd}`. It now has `\input{t1cmr.fd}`. If you use a local file `fonttext.cfg` you will need to make similar changes, as `\input{T1cmr.fd}` will not work as `T1cmr.fd` is no longer in the distribution.

The files affected by this change all have names of the form `*.fd` or `*enc.def`.

### Another input encoding

Thanks to work by Søren Sandmann, the `inputenc` package now supports the IBM codepage 865 used in Scandinavia.

### Better user-defined math display environments

Suppose that you want to define an environment for displaying text that is numbered as an equation. A straightforward way to do this is as follows:

```
\newenvironment{texreqn}
{\begin{equation}
 \begin{minipage}{0.9\linewidth}}
{\end{minipage}
\end{equation}}
```

However, if you have tried this then you will probably have noticed that it does not work perfectly when used

in the middle of a paragraph because an inter-word space appears at the beginning of the first line after the environment.

There is now an extra command (with a very long name) available that you can use to avoid this problem; it should be inserted as shown here:

```
\newenvironment{texreqn}
{\begin{equation}
 \begin{minipage}{0.9\linewidth}}
{\end{minipage}
\end{equation}
\ignorespacesafterend}
```

### Docstrip improvements

The `docstrip` program that is used to unpack the L<sup>A</sup>T<sub>E</sub>X sources has undergone further development. The new version should be able to process all old ‘batchfiles’ but it allows a simpler syntax in new ‘batchfiles’ (no need to define `\def\batchfile{...}`).

It also allows ‘target’ directories to be specified when writing files. This directory support is disabled by default unless activated in a local `docstrip.cfg` configuration file. See `docstrip.dtx` for details.

### AMS L<sup>A</sup>T<sub>E</sub>X update

Since the last L<sup>A</sup>T<sub>E</sub>X release in June, the American Mathematical Society have re-issued the ‘AMS L<sup>A</sup>T<sub>E</sub>X’ classes and packages, fixing several reported problems.

### Graphics package update

The L<sup>A</sup>T<sub>E</sub>X color and graphics packages have been updated slightly, principally to support more dvi drivers, see the readme file in the graphics distribution.

### EC Fonts released

The first release of the Extended Computer Modern fonts has just been made. (In January 1997.)

This release of L<sup>A</sup>T<sub>E</sub>X does *not* default to these ‘ec’ fonts as its T1 encoded fonts. By default it will use the ‘dc’ fonts if the T1 encoding is requested.

As noted in `install.txt` you may run T<sub>E</sub>X on the install file `ec.ins` *after* unpacking the base distribution but *before* making the L<sup>A</sup>T<sub>E</sub>X format. This will produce suitable ‘fd’ files making L<sup>A</sup>T<sub>E</sub>X (including, for the first time, the `slides` class) use the ‘ec’ fonts as the default T1 encoded font set.



# L<sup>A</sup>T<sub>E</sub>X News

Issue 7, June 1997

## *T1 encoded Computer Modern fonts*

As in the last release the base L<sup>A</sup>T<sub>E</sub>X distribution contains three different sets of ‘fd’ files for T1 encoded fonts.

In this release the default installation uses `ec.ins` and so installs files suitable for the current ‘EC fonts’ distribution. If you have still not updated to the EC fonts and are using the earlier test versions, known as DC then you should unpack `newdc.ins` (for DC release 1.2 or later) or `olddc.ins` (for the original releases of the DC fonts). This should be done after unpacking `unpack.ins` but before making the format by running `initEX` on `latex.ltx`. There are further details in `install.txt`.

## *T1 encoded Concrete fonts*

The Metafont sources for T1 encoded ‘Concrete’ fonts have been removed from the `mfns` distribution as they were based on the now obsolete DC fonts release 1.1. Similarly the `cmextra.ins` install file in the base distribution no longer generates fd files for the ‘Concrete’ fonts. To use these fonts in either T1 or OT1 encoding it is recommended that you obtain Walter Schmidt’s `ccfonts` package and fonts from CTAN `macros/latex/contrib/supported/ccfonts`.

## *Further input encodings*

Two more `inputenc` packages have been added: for `latin5`, thanks to H. Turgut Uyar; and for `latin3`, thanks to Jörg Knappen.

## *Normalising spacing after punctuation*

The command `\normalsfcodes` was introduced at the last patch release. This is normally given the correct definition automatically and so need not be explicitly set. It is used to correct a problem, reported by Donald Arseneau, that punctuation in page headers has always (in all known T<sub>E</sub>X formats) been potentially incorrect if the page break happens while a local setting of the space codes (for instance by the command `\frenchspacing`) is in effect. A common example of this happening in L<sup>A</sup>T<sub>E</sub>X is in the `verbatim` environment.

## *Accessing Bold Math Symbols*

The tools distribution contains a new package, `bm`, which defines a command `\bm` that allows individual bold symbols to be accessed within a math expression

(in contrast to `\boldmath` which makes whole math expressions default to bold fonts). It is more general than the existing `ambsy` package; however, to ease the translation of documents between these two packages, `bm` makes `\boldsymbol` an alias for `\bm`.

This package was previously made available from the ‘contrib’ area of the CTAN archives, and as part of Y&Y’s L<sup>A</sup>T<sub>E</sub>X support for the MathTime fonts.

## *Policy on standard classes*

Many of the problem reports we receive concerning the standard classes are not concerned with bugs but are suggesting, more or less politely, that the design decisions embodied in them are ‘not optimal’ and asking us to modify them.

There are several reasons why we have decided not to make such changes to these files.

- However misguided, the current behaviour is clearly what was intended when these classes were designed.
- It is not good practice to change such aspects of ‘standard classes’ because many people will be relying on them.

We have therefore decided not to even consider making such modifications, nor to spend time justifying that decision. This does not mean that we do not agree that there are many deficiencies in the design of these classes, but we have many tasks with higher priority than continually explaining why the standard classes for L<sup>A</sup>T<sub>E</sub>X cannot be changed.

We would, of course, welcome the production of better classes, or of packages that can be used to enhance these classes.

## *New addresses for TUG*

For information about joining the T<sub>E</sub>X Users Group, and about lots of other L<sup>A</sup>T<sub>E</sub>X-related matters, please contact them at their new address:

T<sub>E</sub>X Users Group, P.O. Box 1239,  
Three Rivers, CA 93271-1239, USA  
Fax: +1 209 561 4584  
E-mail: [tug@mail.tug.org](mailto:tug@mail.tug.org)  
URL: <http://www.tug.org/>

# L<sup>A</sup>T<sub>E</sub>X News

Issue 8, December 1997

## *New supported font encodings*

Two new font encodings are supported as options to the `fontenc` package:

**OT4** This is a seven-bit encoding designed for Polish. The L<sup>A</sup>T<sub>E</sub>X support was developed by Mariusz Olko.

**TS1** This is the ‘Text Companion Encoding’; it contains symbols designed to be used in text, as opposed to mathematical formulas, and some accents designed for uppercase letters. It is currently supported by the ‘tc’ fonts, which match the T1 encoded ‘ec’ text fonts. A subset of the glyphs in this encoding is supported by virtual fonts distributed with the PostScript font metrics on the CTAN archives. (This is the ‘8c’ encoding in Karl Berry’s fontname scheme.) The `textcomp` package provides access to this encoding but here is a warning to current users of that package: some of the internal names for the characters have changed.

## *New input encodings*

These additions to the `inputenc` package are `decmulti` (the DEC Multinational Character Set, contributed by M. Y. Chartoire) and `cp1250` (an MS-Windows encoding for Central and Eastern Europe, contributed by Marcin Woliński). There is also a `cp1252` encoding that is identical to `ansinew`.

## *Tools*

The `calc` package (used in many examples in *The L<sup>A</sup>T<sub>E</sub>X Companion*) has been contributed to this distribution by Kresten Krab Thorup and Frank Jensen. This is essentially the same as the version that has been available from the CTAN archives for some time, with one minor change: to use L<sup>A</sup>T<sub>E</sub>X-style error messages. It enables the use of arithmetic expressions within arguments to standard L<sup>A</sup>T<sub>E</sub>X commands where a length or a counter value is required. For example:

```
\setcounter {page} { \value{page} * 2 + 1 }
\parbox { 3in - ( 2mm + \textwidth / 9 ) }
```

There have also been some improvements to several other packages in this collection. In particular, `bm` now works correctly with constructions such as `\bm{f’}` involving ‘ or other characters which use T<sub>E</sub>X’s special “`\mathcode"8000`” feature. Also, `multicol` sets the length `\columnwidth` to an appropriate value; this enables it to work with classes that support two-column setting, e.g., the AMS classes.

## *Graphics*

The special `oztex.def` driver file has been removed, and OzT<sub>E</sub>X support has been merged with dvips, following advice from Andrew Trevorrow about OzT<sub>E</sub>X 3.x.

The `keyval` package has had some internal improvements: to use L<sup>A</sup>T<sub>E</sub>X format error messages; and to avoid ‘# doubling’. This latter change means that the `command` key for the `graphicx` version of `\includegraphics` should now be used with one # rather than two. For example, `command = ‘gunzip #1`. Fortunately this key is almost never used in practice, so few if any documents should be affected by this change.

## *L<sup>A</sup>T<sub>E</sub>X3 experimental programming conventions*

As announced at the T<sub>E</sub>X Users Group meeting (Summer 1997), a group of highly experimental packages will soon be released to allow experienced T<sub>E</sub>X programmers to experiment with, and comment on, a proposed set of syntax conventions and basic data-types that might form the basis for programming large scale projects in T<sub>E</sub>X. They will be located in this CTAN directory:

`CTAN:macros/latex/packages/exp13`

The documentation of this material is as follows: individual package files provide outline, draft documentation; there is an article that gives an overview of the syntax and related concepts; there is a `readme.txt` file containing a brief description of the collection.

All aspects of these packages are liable, indeed likely, to change. They should not be used at this stage for anything that requires a stable system. However, we do encourage people to experiment with these packages, and to send comments on them to the L<sup>A</sup>T<sub>E</sub>X-L mailing list. To subscribe to this list, mail to:

`listserv@urz.uni-heidelberg.de`

the following one line message:

`subscribe LATEX-L <first-name> <second-name>`

# L<sup>A</sup>T<sub>E</sub>X News

Issue 9, June 1998

## *New math font encodings*

A joint working group of the T<sub>E</sub>X Users Group and the L<sup>A</sup>T<sub>E</sub>X3 Project is developing a new 8-bit math font encoding for T<sub>E</sub>X. It is designed to overcome several limitations and implementation problems of the old math font encodings and to simplify switching between different sets of math fonts, much as the L<sup>A</sup>T<sub>E</sub>X font selection interface has simplified switching between text fonts.

Since the work on this project relies entirely on volunteer work, we cannot give a specific release date yet. However, a prototype implementation already exists. This contains several sets of virtual fonts, some L<sup>A</sup>T<sub>E</sub>X packages and a kernel module; we hope to integrate it into the main L<sup>A</sup>T<sub>E</sub>X distribution for the next release.

Documents using only standard L<sup>A</sup>T<sub>E</sub>X commands for math symbols should not be affected by switching to the new math font encodings. However, documents, classes or packages making specific assumptions about the encoding of math symbol fonts are likely to break.

Further information about the Math Font Group may be found on the World Wide Web at <http://www.tug.org/twg/mfg/>.

## *A new math accent*

A new math accent, `\mathring`, has been added. This is a math mode version of the ring accent (°) which is available in text mode with the command `\r`.

## *Extended `\DeclareMathDelimiter`*

The command `\DeclareMathDelimiter` has been extended. Normally this command takes six arguments. Previously, when being used to declare a character (such as `[]`) as a delimiter, a variant form was used with only five arguments. The argument specifying the default ‘math class’ was omitted. Now the full six-argument form may be used in this case. The extra information is used to implicitly declare the character via `\DeclareMathSymbol` for use when the symbol is not used with `\left` or `\right`.

The old five-argument form is detected and will work as before.

## *Tools distribution*

The `multicol` package now supports the production of multiple columns without balancing the last page. To get this effect use the `multicols*` environment.

The `layout` package was partly recoded by Hideo Umeki to display page layout effects in a better way.

As suggested by Donald Arseneau, the `calc` package was extended to support the new commands `\widthof{text}`, `\heightof{text}`, and `\depthof{text}` within a `calc`-expression. At the same time we modified a few kernel commands so that `calc`-expressions can now be used in various useful places such as the dimension arguments to the `tabular` environment and the `\rule` command. For many other standard L<sup>A</sup>T<sub>E</sub>X commands this was already possible.

## *Support for Cyrillic encodings*

We are very pleased that, after a lengthy period of development, a set of fonts, encodings and support files for using L<sup>A</sup>T<sub>E</sub>X with Cyrillic characters will soon be available.

Test versions of the ‘LH’ fonts for these Cyrillic encodings, based on the Computer Modern design, are available from CTAN archives in the directory `fonts/cyrillic/lh-test`. The L<sup>A</sup>T<sub>E</sub>X support files (by Werner Lemberg and Vladimir Volovich) are also available from CTAN archives in `macros/latex/contrib/supported/t2`

## *Default docstrip header*

Many L<sup>A</sup>T<sub>E</sub>X users now distribute packages in documented source form using the `docstrip` system. Docstrip allows a header to be placed on generated package files, suitable for giving copyright information, or distribution conditions.

We have changed the default version of this header so that it allows stripped files to be distributed in ready-to-run installations such as the T<sub>E</sub>XLive CD. If you use the default header for distributing your files you should check that the new copyright text is acceptable to you. The file `docstrip.dtx` explains how to produce your own header if you wish to do so.

# L<sup>A</sup>T<sub>E</sub>X News

Issue 10, December 1998

## *Five years of L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>*

Since this is the 10th edition of L<sup>A</sup>T<sub>E</sub>X News, the (no longer) New Standard L<sup>A</sup>T<sub>E</sub>X must have hit the streets almost this long ago. In fact it was only the beta-version that some people got just in time for Christmas 1993, and since then there has been a lot of tidying-up and smoothing of rough edges (not to mention a few bug fixes!).

Maybe it is time for something more radically different to emerge and be hungrily adopted by the world; but don't panic, we shall be maintaining what you have now for a long time yet. Amongst the more polite things that have been written about our efforts, we found that this quote (somewhat censored to protect the guilty) well reflects some of our feelings about working on L<sup>A</sup>T<sub>E</sub>X over the years: *the mere existence of L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> is a great miracle.*

## *Restructuring the L<sup>A</sup>T<sub>E</sub>X distribution*

Since the (once) 'new' standard L<sup>A</sup>T<sub>E</sub>X has reached such a venerable age, we are reviewing the way in which the system is presented to the world.

An early intention is to define, given the wide variety of good packages now available, what now constitutes a useful installation of L<sup>A</sup>T<sub>E</sub>X. We also hope that such a definition will help document portability if it leads to a future in which a L<sup>A</sup>T<sub>E</sub>X class designer can reasonably assume that a known list of facilities will be there for all users (so that each class need not supply them).

As a first small step towards this definition, we shall replace the `latex/packages` subdirectory on CTAN. This directory was a curious mixture of the important, such as the L<sup>A</sup>T<sub>E</sub>X `tools`, that any self-respecting L<sup>A</sup>T<sub>E</sub>X installation ought to have, and the esoteric or experimental.

The esoterica from `packages` will be moved to new locations, as follows:

```
expl3 to latex/exptl/project
mfnfss to latex/contrib/supported/mfnfss
```

The subdirectory that replaces `packages` will be called `latex/required`; all the other sub-directories of `packages` will be moved there.

## *L<sup>A</sup>T<sub>E</sub>X Project on the Internet*

A new `latex-project.org` domain has been registered. The web site is not yet fully functional but the old L<sup>A</sup>T<sub>E</sub>X pages from CTAN are available at <http://www.latex-project.org/> and the L<sup>A</sup>T<sub>E</sub>X bug reporting address has been changed to `latex-bugs@latex-project.org`.

## *Restructuring the L<sup>A</sup>T<sub>E</sub>X package licenses*

Several people have requested an easy mechanism for the distribution of L<sup>A</sup>T<sub>E</sub>X packages and other software "under the same conditions as L<sup>A</sup>T<sub>E</sub>X". The old `legal.txt` file was unsuitable as a general licence as it referred to specific L<sup>A</sup>T<sub>E</sub>X authors, and to specific files.

Therefore, in this release `legal.txt` contains just the copyright notice and a reference to the new *L<sup>A</sup>T<sub>E</sub>X Project Public License* (LPPL) for the distribution and modification conditions. The `tools`, `graphics`, and `mfnfss` packages also now refer to this license in their distribution notices.

## *Support for Cyrillic encodings*

Basic Cyrillic support, as announced in L<sup>A</sup>T<sub>E</sub>X News 9, is now finally an official part of L<sup>A</sup>T<sub>E</sub>X. It includes support for the following standard Cyrillic font encodings (this list may grow): T2A T2B T2C X2.

It also includes various Cyrillic input encodings (20 in total, including commonly used variants and Mongolian Cyrillic encodings). This provides platform independent and sophisticated basic support for high-quality typesetting in various Cyrillic-based languages.

For further information see the file `cyrguide.tex`.

## *Tools distribution*

The `varioref` package has been extended to support textual page references to a range of objects: e.g., if `eq-first` and `eq-last` are the label names for the first and last equation in a sequence, then you can now write

```
see~\vrefrange{eq-first}{eq-last}
```

This results in different text depending on whether both labels fall on the same page.

Some additional user commands, as well as building-blocks for writing private extensions, are described in the accompanying documentation.

# L<sup>A</sup>T<sub>E</sub>X News

Issue 11, June 1999

## *Back in sync*

The last release of L<sup>A</sup>T<sub>E</sub>X was delayed even longer than you have come to expect. We hope that it proved worth waiting for. It required a major integration of the code from several people and, independently, the introduction of the LPPL (see L<sup>A</sup>T<sub>E</sub>X News 10) plus several related changes to our internal systems. It therefore seemed sensible to wait until everything was complete rather than do things in too much hurry.

This seem to have been a successful strategy as the recent patch release was related to an isolated change that was done many months previously. If this release does not appear a lot closer to its nominal date then ... well, you will not be reading this sentence!

## *Yearly release cycles*

With the year 2000 rapidly approaching, we intend to switch to a release frequency of just one per year (with patches if necessary) for the core of L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub>. These days the system is sufficiently stable that the original update policy is costing everybody more time than is now warranted.

## *LPPL update*

Thanks to extensive and valuable input from Matt Swift ([swift@alum.mit.edu](mailto:swift@alum.mit.edu)) we now have a clearer and more detailed form of the L<sup>A</sup>T<sub>E</sub>X Project Public Licence. This release contains both the original version (in `lppl-1-0.txt`) and the updated version, LPPL 1.1.

## *The future of SliT<sub>E</sub>X*

We still get a very small trickle of reports about this part of the system (if you are no longer able to recall L<sup>A</sup>T<sub>E</sub>X 2.09 then you will know it as the `slides` class). We have not classified them (in our minds at least) as bugs since we have always known that there are many problems with this class. It is clear to us that the only sensible action would be to redesign the system completely; in particular, to remove much of its complexity whose purpose is to support 10-year-old overlay technology. However, this would take a lot too much time and would be completely out of proportion to its current usage.

We are therefore planning to make the `slides` class unsupported in the sense that any problem related to the use of invisible fonts is considered to be a feature (The L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> manual by Leslie Lamport doesn't even

describe this part of the class any more). Of course, if it still has its enthusiasts then we are happy to cede it to their loving care (somewhat like a preserved steam locomotive, in some parts of the world).

## *Fontenc package peculiarities*

The `\usepackage` interface normally ensures that a package is loaded only once. The `fontenc` package has become an exception to this rule: it can be loaded several times using different options, e.g., allowing the user to add a font encoding in the preamble. This comes at a price for package writers: the low-level commands (see `ltxclass.dtx`) used to check if a package was loaded, and with which options, do not work for the `fontenc` package.

## *New math font encodings*

As we announced in L<sup>A</sup>T<sub>E</sub>X News 9, a joint working group of the T<sub>E</sub>X Users Group and the L<sup>A</sup>T<sub>E</sub>X3 Project has developed a new 8-bit math font encoding for T<sub>E</sub>X. The reason why this work is not yet released is because of other exciting developments in the world of math fonts and math characters. It is obviously wise to ensure that the encoding work is fully integrated with the available fonts.

Those interested are reminded that further information about the Math Font Group may be found on the World Wide Web at:

<http://www.tug.org/twg/mfg/>.

## *Tools distribution*

The `multicol` package has now got a small but useful extension which allows you to force a column break where this is really necessary. This is done with the command `\columnbreak`, which can be used like `\pagebreak` (e.g., within paragraphs) except that it cannot have an optional argument and thus it always forces a new column.

## *Coming soon*

Major work on a new class file structure to support flexible designs is well under way; some of this work will be presented at the TUG'99 conference in Vancouver, Canada. With a bit of luck much of this work could be ready for integration into the next release—so watch this space!

# L<sup>A</sup>T<sub>E</sub>X News

Issue 12, December 1999

## *LPPL update*

Since the release of the L<sup>A</sup>T<sub>E</sub>X Project Public Licence version 1.1, we have received a small number of queries which resulted in some minor changes to improve the wording or explain the intentions better. As a consequence this release now contains LPPL 1.2 in the file `lppl.txt` and the previous versions as `lppl-1-0.txt` and `lppl-1-1.txt`.

## *fixltx2e package*

This package provides fixes to L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> which are desirable but cannot be integrated into the L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> kernel directly as they would produce a version incompatible to earlier releases (either in formatting or functionality).

By having these fixes in the form of a package, users can benefit from them without the danger that their documents will fail, or produce unexpected results, at other sites; this works because a document will contain a clear indication (the `\usepackage` line, preferably with a required date) that at least some of these fixes are required to format it.

## *Outcome of TUG '99 (Vancouver)*

The slides from the TUG'99 presentation we gave on *a new interface for L<sup>A</sup>T<sub>E</sub>X class designers* are available from the L<sup>A</sup>T<sub>E</sub>X Project website; look for the file `tug99.pdf` at:

<http://www.latex-project.org/talks/>

Please note that this document was intended only to be informal “speaker’s notes” for our own use. We decided to make them available (the speaker’s notes as well as the slides that were presented) because several people requested copies after the talk. However, they are *not* in a polished copy-edited form and are not intended for publication.

Prototype implementations of parts of this interface are now available from:

<http://www.latex-project.org/code/experimental/>

We are continuing to add new material at this location so as to stimulate further discussion of the underlying concepts. As of December 1, 1999 the following parts can be downloaded.

**xparse** Prototype implementation of the interface for declaring document command syntax. See the `.dtx` files for documentation.

**template** Prototype implementation of the template interface (needs parts of **xparse**).

The file `template.dtx` in that directory has a large section of documentation at the front describing the commands in the interface and giving a ‘worked example’ building up some templates for caption formatting.

**xcontents** Interface description for table of contents data (no code yet). Coding examples have been thoroughly discussed on the `latex-l` list.

**xfootnote** Working examples for generating footnotes, etc. Needs **xparse** and **template**.

All examples are organised in subdirectories and additionally available as **gzip tar** files.

Please remember that this material is intended only for experimentation and comments; thus any aspect of it, e.g., the user interface or the functionality, may change and, in fact, is very likely to change. For this reason it is explicitly forbidden to place this material on CD-ROM distributions or public servers.

These concepts, as well as their implementation, are under discussion on the list `LATEX-L`. You can join this list, which is intended solely for discussing ideas and concepts for future versions of L<sup>A</sup>T<sub>E</sub>X, by sending mail to `listserv@URZ.UNI-HEIDELBERG.DE` containing the line

SUBSCRIBE LATEX-L *Your Name*

This list is archived and, after subscription, you can retrieve older posts to it by sending mail to the above address, containing a command such as:

GET LATEX-L LOGyy<sup>mm</sup>

where `yy`=Year and `mm`=Month, e.g.

GET LATEX-L LOG9910

for all messages sent in October 1999.

# L<sup>A</sup>T<sub>E</sub>X News

Issue 13, June 2000

## Yearly release cycle

We announced in *L<sup>A</sup>T<sub>E</sub>X News 11* that we intended to switch to a 12-monthly release schedule. With the present (June 2000) release, this switch is being made: thus the next release of L<sup>A</sup>T<sub>E</sub>X will be dated June 2001. We shall of course continue, as in the past, to release patches as needed to fix significant bugs.

## PSNFSS: Quote of the Month

You should say in the L<sup>A</sup>T<sub>E</sub>X News that Walter Schmidt has taken over PSNFSS from me. It gives me a certain pleasure to be able to draw a line under that part of my life...

Sebastian Rahtz

The PSNFSS material, which supports the use of common PostScript fonts with L<sup>A</sup>T<sub>E</sub>X, has been thoroughly updated. Most noticeably, the **mathpple** package, which used to be distributed separately, is now part of the basic PSNFSS bundle; this package provides mathematical typesetting with the Palatino typeface family. In addition, numerous bugs and flaws have been fixed and the distribution has been ‘cleaned up’. The file **changes.txt** contains a detailed list of these changes.

The documentation (in **psnfss2e.pdf**) has been completely rewritten to provide a comprehensive introduction to the use of PostScript fonts.

Notice that the new PSNFSS needs updated files for font metrics, virtual fonts and font definitions. If you received the new version (8.1) as part of a complete T<sub>E</sub>X system then these new font files should also have been installed. However, if you intend to install or update PSNFSS yourself, please read the instructions in the file **00readme.txt** of the new PSNFSS distribution.

Support for commercial PostScript fonts, such as Lucida Bright, has been removed from the basic distribution; it is now available from CTAN: <http://www.tex.ac.uk/tex-archive/macros/latex/contrib/supported/psnfssx>.

## New AMS-L<sup>A</sup>T<sub>E</sub>X

Version 2.0 of AMS-L<sup>A</sup>T<sub>E</sub>X was released on December 1, 1999. It can be obtained via <ftp://ftp.ams.org/pub/tex/> or <http://www.ams.org/tex/amslatex.html>, as well from CTAN: <http://www.tex.ac.uk/tex-archive/macros/latex/required/amslatex>.

This release consists chiefly of bug fixes and consolidation of the existing features. The division of

AMS-L<sup>A</sup>T<sub>E</sub>X into two main parts (the math packages; the AMS document classes) has been made more pronounced. The files **diffs-m.txt**, **diffs-c.txt**, **amsmath.faq**, and **amscs.faq** describe the changes and address some common questions.

The primary documentation files remain **amslatex.tex**, for the amsmath package, and **instr-l.tex**, for the AMS document classes. The documentation for the **amsthm** package, however, has been moved from **amslatex.tex** to a separate document **amsthdoc.tex**.

## New input encoding latin4

The package **inputenc** has, thanks to Hana Skoumalová, been extended to cover the **latin4** input encoding; this covers Baltic and Scandinavian languages as well as Greenland Inuit and Lappish.

## New experimental code

In *L<sup>A</sup>T<sub>E</sub>X News 12* we announced some ongoing work towards a ‘Designer Interface for L<sup>A</sup>T<sub>E</sub>X’ and we presented some early results thereof. Since then, at Gutenberg 2000 in Toulouse and TUG 2000 in Oxford, we described a new output routine and an improved method of handling vertical mode material between paragraphs. In combination these support higher quality *automated*<sup>1</sup> page-breaking and page make-up for complex pages—the best yet achieved with T<sub>E</sub>X!

A paper describing the new output routine is at <http://www.latex-project.org/papers/xo-pfloat.pdf>. All code examples and documentation are available at <http://www.latex-project.org/code/experimental/>.

This directory has been extended to contain

**galley** Prototype implementation of the interface for manipulating vertical material in galleys.

**xinitials** Prototype implementation of the interface for paragraph initials (needs the **galley** package).

**xtheorem** Contributed example using the **template** package to provide a designer interface for theorem environments.

**xoutput** A prototype implementation of the new output routine as described in the **xo-pfloat.pdf** paper. Expected availability: at or shortly after the TUG 2000 conference.

---

<sup>1</sup>The stress here is on automated!



# L<sup>A</sup>T<sub>E</sub>X News

Issue 14, June 2001

## Future releases

We are currently exploring how to best support the very large community of individuals, organisations and enterprises that depend on the robustness and availability of the current standard L<sup>A</sup>T<sub>E</sub>X distribution. The results of this may lead to some changes in the regular release schedule and the handling of bug reports during the next year.

## New release of Babel (required)

Earlier this year a new release of Babel (3.7) became available. You can read about its new features in <http://www.ctan.org/tex-archive/macros/latex/required/babel/announce.txt>

One of the bugs that got fixed in this release deals with how labels are handled by L<sup>A</sup>T<sub>E</sub>X. Because this part of the kernel is modified by `babel`, the relevant changes need to be coordinated. Therefore to use Babel with this release of L<sup>A</sup>T<sub>E</sub>X you will need to update your version of `babel` to at least 3.7.

## New input encoding latin9

The package `inputenc` has, thanks to Karsten Tinnfeld, been extended to cover the `latin9` input encoding. The ISO-Latin 9 encoding is a useful modern replacement for ISO-Latin 1 that contains a few characters needed for French and Finnish. Of wider interest, it also contains the euro currency sign; this could be the killer argument for many 8-bit texts to use Latin-9 in the future.

According to a Linux manpage, ISO Latin-9 supports Albanian, Basque, Breton, Catalan, Danish, Dutch, English, Estonian, Faroese, Finnish, French, Frisian, Galician, German, Greenlandic, Icelandic, Irish Gaelic, Italian, Latin, Luxemburgish, Norwegian, Portuguese, Rhaeto-Romanic, Scottish Gaelic, Spanish and Swedish. The characters added in `latin9` are (in L<sup>A</sup>T<sub>E</sub>X notation):

```
\texteuro \v S \v s \v Z \v z \OE \oe \" Y
They displace the following characters from latin1:
\textcurrency \textbrokenbar \"{} \'{} \c{}
\textonequarter \textonehalf \textthreequarters
```

## New tools

The new package `trace` provides many commands to control L<sup>A</sup>T<sub>E</sub>X's tracing and debugging output, including the excellent new information available with  $\epsilon$ -T<sub>E</sub>X such as the extremely useful tracing of local assignments. You will find it in the tools distribution.

It offers the command `\tracelon`, which is similar to `\tracingall` but suppresses uninteresting stuff such as font loading by NFSS (which can go on for pages if you are unlucky). It also offers `\traceoff` to ... guess what! Full details are in the documented source file, `trace.dtx`.

In the base `ifthen` package we have added the uppercase synonyms `\NOT` `\AND` and `\OR`.

## New experimental code

In *L<sup>A</sup>T<sub>E</sub>X News 12* we announced some ongoing work towards a 'Designer Interface for L<sup>A</sup>T<sub>E</sub>X' and we presented some early results thereof. Since then, at Gutenberg 2000 in Toulouse and TUG 2000 in Oxford, we described a new output routine and an improved method of handling vertical mode material between paragraphs. In combination these support higher quality *automated*<sup>1</sup> page-breaking and page make-up for complex pages—the best yet achieved with T<sub>E</sub>X!

More recently we have added material to handle the complex front matter requirements of journal articles; this was presented at Gutenberg 2001 in Metz.

A paper describing the new output routine is at <http://www.latex-project.org/papers/xo-pfloat.pdf>. All code examples and documentation are available at <http://www.latex-project.org/code/experimental>

This directory has been extended to contain the following.

**galley** Prototype implementation of the interface for manipulating vertical material in galleys.

**xinitials** Prototype implementation of the interface for paragraph initials (needs the `galley` package).

**xtheorem** Contributed example using the `template` package to provide a designer interface for theorem environments.

**xor** A prototype implementation of the new output routine as described in the `xo-pfloat.pdf` paper.

**xfrontm** A prototype version of the new font matter interface.

---

<sup>1</sup>The stress here is on *automated*!



# L<sup>A</sup>T<sub>E</sub>X News

Issue 15, December 2003

## *Anniversary release*

Yes, it's now 10 years since the first release in this series and, for Knuthists, this release also contains *Issue 16*!

Meanwhile this *Issue 15* describes the major new features in the current release whilst *Issue 16* looks a little way into the future of L<sup>A</sup>T<sub>E</sub>X.

## *LPPL – new version*

Most importantly, there is now a new version, 1.3, of the L<sup>A</sup>T<sub>E</sub>X Project Public Licence. Many of you will be thrilled to know that, following the exchange of over 1600 e-mail messages dissecting various aspects of its philosophy such as ‘how many angels can appear in the name of a file before it becomes non-free’, this version is now officially a DFSG (Debian Free Software Guidelines) approved license. The discussions start at <http://lists.debian.org/debian-legal/2002/debian-legal-200207/threads.html> with high traffic throughout August to October 2002 and further heated discussions starting in April 2003 and concluding around June at <http://lists.debian.org/debian-legal/2003/debian-legal-200306/msg00206.html>.

The important features of the new version are useful clarifications in the wording, and revised procedures for making a change to the Current Maintainer of a package. Special thanks to all those people from Debian Legal who worked constructively with us on this onerous task, especially but not exclusively Jeff Licquia and Branden Robinson.

## *Small updates to varioref*

The English has been corrected in `\reftextbefore` (an incompatible change). There are other extensions such as `\labelformat`, `\Ref`, `\Vref` and `\vpagerefnum`. Some Dutch text has also been changed and two new options added: `slovak` and `slovene`.

## *New and more robust commands*

Many of the math mode commands for compound symbols have been made robust and a new robust command has been added: `\nobreakdashes`. This last is a low-level command, borrowed from the `amsmath` package, for use only before hyphens or dashes. It prevents the line break that is normally allowed after the following sequence of dashes.

## *Fixing font sizes*

The new `fix-cm` package, by Walter Schmidt, changes the CM font definition (`.fd`) files so that similar design sizes are used in both the OT1 and T1 encodings.

## *Font encodings*

A number of options have been added to the `textcomp` package, enabling only available glyphs to be used. Also, the ‘NFSS font families’ are now divided into five different groups according to the subset of glyphs each provides from the full collection of symbols in the TS1 encoding. Given sufficient information about a font family `textcomp` will use this in order to limit the typesetting to those glyphs that are available.

Use of this mechanism has also enhanced `\oldstylenums` to use the current font if possible.

## *Displaying font tables*

With the `nfssfont` package you can now specify the font to display by giving its ‘NFSS classification’, rather than needing to know its external font file’s name. It is also now possible to generate large collections of font tables in batch mode by providing a suitable input file.

## *New input encodings*

The `inputenc` package has been extended as follows: `macce` input encoding (Apple Central European), thanks to Radek Tryc and Marcin Wolinski; `cp1257` for Baltic languages; `latin10`, thanks to Ionel Ciobîcă. The euro symbol has by now been added to several encodings: `ansinew`, `cp1250` and `cp1252` (which also has another addition), whilst `cp858` adds it to `cp850`.

## *Unicode input*

Partial, experimental support for text files that use the Unicode encoding form UTF-8 is now provided by the option `utf8` for the `inputenc` package.

The only Unicode text file characters supported by the current version are those based on the most common inputs for glyphs from the small collection of standard L<sup>A</sup>T<sub>E</sub>X Latin encodings.

## *And finally ... pict2e*

The old, non-functional version of this package has been removed as there is now a fully working version from Hubert Gäßlein and Rolf Niepraschk. It is described in *The L<sup>A</sup>T<sub>E</sub>X Manual*.

# L<sup>A</sup>T<sub>E</sub>X News

Issue 16, December 2003

## *Anniversary news*

This anniversary *Issue 16* takes a brief look into the future work of the L<sup>A</sup>T<sub>E</sub>X3 Project Team, both short and longer range. Please let us know if you want to get involved with us in any of this work (see below).

An overview of the 10th Anniversary Release, dated 2003/12/01, is can be found in *Issue 15*.

## *TLC2: The L<sup>A</sup>T<sub>E</sub>X Companion – 2nd edition!*

Since you are reading this newsletter, there is a good chance that you, or a friend, has already bought this encyclopedic volume: the incomparable Second Edition of this work that is every L<sup>A</sup>T<sub>E</sub>Xie's ultimate lucky charm.

If by some chance you have not yet purchased your own copy then get into training, get shopping, and get flexing your muscles (both physical—it's 1100+ pages, and intellectual) by using it to discover masses of invaluable 'insider information' about:

- the latest release of Standard L<sup>A</sup>T<sub>E</sub>X;
- over 200 extension packages;
- plus related software and systems.

For more information on this all new (??... OK, not *all*, but over 90%!), all accurate (we hope!) 10th Anniversary Edition, check out <http://www.awprofessional.com/titles/0201362996>.

## *Future maintenance*

We are currently exploring how best to support the very large and rapidly growing community of individuals, organisations and enterprises that depend on the robustness and availability of the current standard L<sup>A</sup>T<sub>E</sub>X distribution. Although we remain firmly resolved not to make changes in the base distribution (the kernel) of Standard L<sup>A</sup>T<sub>E</sub>X, there is still much that needs doing to maintain its reliability and utility and to keep up the necessary level of communication with users and supporters. Also, as with all advanced software systems, bugs are still turning up occasionally so some fixes are still essential.

One major impediment to providing adequate service levels in this area is, of course, the difficulties inherent in obtaining the time and commitment of skilled minds—hence the appeal above to anyone interested in getting involved.

## *LPPL certification*

There are still some outstanding diplomatic tasks around the L<sup>A</sup>T<sub>E</sub>X Project Public Licence: these include e.g., getting it 'OSF certified' and ensuring that it gains more support and wider use, even in the FSF world where it has long been tolerated.

## *Use of $\varepsilon$ -T<sub>E</sub>X/pdfT<sub>E</sub>X*

We expect that within the next two years, releases of L<sup>A</sup>T<sub>E</sub>X will change modestly in order to run best under an extended T<sub>E</sub>X engine that contains the  $\varepsilon$ -T<sub>E</sub>X primitives, e.g.,  $\varepsilon$ -T<sub>E</sub>X or pdfT<sub>E</sub>X. The details of this possible upgrade need further work so we are not making a definite announcement yet.

Although the current release does not *require*  $\varepsilon$ -T<sub>E</sub>X features, we certainly recommend using an extended T<sub>E</sub>X, especially if you need to debug macros.

## *End of 'autoload' support*

As computer systems generally grow in capacity, requirements change and so we believe that the *autoload* variant of L<sup>A</sup>T<sub>E</sub>X is no longer required. Thus, although the code remains it is no longer supported. We hope this does not cause any problems.

## *New models, new code*

In the period 1999–2001 we published many results of our work over the previous decade on the development of new concepts and models for automated typesetting based on T<sub>E</sub>X as the underlying platform. These can be found at <http://www.latex-project.org/papers/> and <http://www.latex-project.org/code/experimental/>.

Since then a very large proportion of the The Team's efforts have been diverted to provide the core author team for TLC2, which provides over 1000 pages of carefully researched and tested documentation of many aspects of the vast world of L<sup>A</sup>T<sub>E</sub>X related software that was developed over that same time period and that continues to grow and improve prodigiously.

Completion of that task ... until TLC3!! ... presents the possibility of getting back to this more exciting development work, or even to more radical work on non-T<sub>E</sub>X-based models and implementations.

Of course, any such ideas are predicated on our ability to organise (with you, we hope) an efficient but responsive maintenance and support system for Standard L<sup>A</sup>T<sub>E</sub>X.

# L<sup>A</sup>T<sub>E</sub>X News

Issue 17, December 2005

## *Project licence news*

The L<sup>A</sup>T<sub>E</sub>X Project Public License has been updated slightly so that it is now version 1.3c. In the warranty section the phrase “unless required by applicable law” has been reinstated, having got lost at some point. Also, it now contains three clarifications: of the difference between “maintained” and “author-maintained”; of the term “Base Interpreter”; and when clause 6b and 6d shall not apply.

Following requests, we now also provide the text of the licence as a L<sup>A</sup>T<sub>E</sub>X document (in the file `lpp1.tex`). This file can be processed either as a stand-alone document or it can be included (without any modification) into another L<sup>A</sup>T<sub>E</sub>X document, e.g., as an appendix, using `\input` or `\include`.

## *New guide on font encodings*

Way back in 1995 work was started on a guide to document the officially allocated L<sup>A</sup>T<sub>E</sub>X font encoding names. However, for one reason or another this guide (named *L<sup>A</sup>T<sub>E</sub>X font encodings*) was, until now, not added to the distribution. It describes the major 7-bit and 8-bit font encodings used in the L<sup>A</sup>T<sub>E</sub>X world and explains the restrictions required of conforming text font encodings. It also lists all the ‘encoding specific commands’ (the LICR or L<sup>A</sup>T<sub>E</sub>X Internal Character Representation) for characters supported by the encodings OT1 and T1.

When the file `encguide.tex` is processed by L<sup>A</sup>T<sub>E</sub>X, it will attempt to typeset an encoding table for each encoding it describes. For this to be possible, L<sup>A</sup>T<sub>E</sub>X must be able to find `.tfm` files for a representative example font for each encoding. If L<sup>A</sup>T<sub>E</sub>X cannot find such a file then a warning is issued and the corresponding table is omitted.

## *Robust commands in math*

The font changing commands in text-mode have been robust commands for years, but the same has not been true for the math versions such as `\mathbf`. While the math-mode commands worked correctly in section heads, they could cause problems in other places such as index entries. With this release, these math-mode commands are now robust in the same way as their text-mode counterparts.

## *Updates of required packages*

Several of the packages in the tools bundle have been updated for this release.

The `xspace` package has some new features. One is an interface for adding and removing the exceptions it knows about and another is that it works with active characters. These remove problems of incompatibility with the `babel` system.

In *L<sup>A</sup>T<sub>E</sub>X News 16* we announced that some packages might begin to take advantage of  $\epsilon$ -T<sub>E</sub>X extensions on systems where these are available: and the latest version of `xspace` does just that. Note also that `fixltx2e` will make use of the facilities in  $\epsilon$ -T<sub>E</sub>X whenever these are present (see below).

The `calc` package has also been given an update with a few extra commands. The commands `\maxof` and `\minof`, each with two brace-delimited arguments, provide the usual numeric max and min operations. The commands `\settototalheight` and `\totalheightof` work like `\settoheight` and `\heightof`. There are also some internal improvements to make `calc` work with some more primitive T<sub>E</sub>X constructs, such as `\ifcase`.

The `varioref` package has acquired a few more default strings but there are still a number of languages for which good strings are still missing.

The `showkeys` package has also been updated slightly to work with more recent developments in `varioref`. Also, it now provides an easy way to define the look of the printed labels with the command `\showkeyslabelformat`.

## *Work on L<sup>A</sup>T<sub>E</sub>X fixes*

The package known as `fixltx2e` has three new additions. A new command `\textsubscript` has been added as a complement to the command `\textsuperscript` in the kernel. Secondly, a new form of `\DeclareMathSizes` that allows all of its arguments to have a dimension suffix. This means you can now use expressions such as `\DeclareMathSizes{9.5dd}{9.5dd}{7.4dd}{6.6dd}`.

The third new addition is the robust command `\TextOrMath` which takes two arguments and executes one of them when typesetting in text or math mode respectively. This command also takes advantage of  $\epsilon$ -T<sub>E</sub>X extensions if available; more specifically, when the  $\epsilon$ -T<sub>E</sub>X extensions are available, it does not destroy kerning between previous letters and the text to be

typeset. The command is also used internally in fixltx2e to resolve a problem with `\fnsymbol`.

Also, further work has been done on reimplementing the command `\addpenalty`, which is used internally in several places: we hope it is an improvement!

### *The graphics bundle*

The `graphics` bundle now supports the `dvipdfmx` post-processor and Jonathan Kew's XETEX program. By support we mean that the `graphics` packages recognize the new options `xetex` and `dvipdfmx` but we do not distribute the respective driver files.

This leads elegantly to a description of the new policy concerning such driver files in the `graphics` bundle. Most driver files for our `graphics` packages are maintained by the developers of the associated post-processor or T<sub>E</sub>X programs. The teams developing these packages are working very hard: their rapid development offers a stark contrast to the current schedule of L<sup>A</sup>T<sub>E</sub>X releases. It is therefore no longer practical for the L<sup>A</sup>T<sub>E</sub>X Team to be responsible for distributing the latest versions of these driver files.

Therefore the installation files for `graphics` have been split: there is now `graphics.ins` to install the package files and `graphics-drivers.ins` for the driver files (located in `drivers.dtx`). There is no need to install all those provided in the file `drivers.dtx`.

Please also note that, as requested by the maintainers of PStricks, we have removed the package `pstcol` as current versions of PStricks make it obsolete.

### *Future development*

The title of this section is a little misleading as it actually describes *current* development. In 1998 the `expl3` bundle of packages was put on CTAN to demonstrate a possible L<sup>A</sup>T<sub>E</sub>X3 programming environment. These packages have been lying dormant for some time while the L<sup>A</sup>T<sub>E</sub>X Project Team were preoccupied by other things such as developing the experimental packages `xor`, `template`, etc., (and also writing that indispensable and encyclopaedic volume, The L<sup>A</sup>T<sub>E</sub>X Companion – 2nd edition).

In October 2004 work on this code base was resumed with the goal of some day turning it into a kernel for L<sup>A</sup>T<sub>E</sub>X3. This work can now also make full use of the widely accepted  $\varepsilon$ -T<sub>E</sub>X extensions. Currently two areas are central to this work.

- Extending the kernel code of L<sup>A</sup>T<sub>E</sub>X3.
- Converting the experimental packages such as `xor`, `template` to use the new syntax internally.

Beware! Development of `expl3` is happening so fast that the descriptions above might be out of date when you read this! If you wish to see what's going on then go to <http://www.latex-project.org/code.html> where you can download fully working code (we hope!).